

SS4000 Series


SS4013MG-12M-WGG01E



Features

- Web based operation, flexible for debugging and deployment;
- AI enabled classification tool, ease to use;
- Integrated 1 dimensional and 2 dimensional code reading;
- Built in pattern match tool to realize presence/absence, front/back, counting and other inspection tools;
- Various GPIO interface, support numerous communication protocols;
- Auto focus, one click auto-focusing;
- IP65 protection level;

Dimensions (mm)



Specification

Model		SS4013MG-12M-WGG01E
Basic	Resolution	1280 × 1024
	Max. Frame rate	60 fps
	Shutter Mode	Global
	Mono/Color	Mono
	Lens Mount	M12, auto focus
	Trigger Mode	Software/external/free run etc.
	Software	EasyVS
	Certifications	CE, UKCA, KC
	Function	AI Tool: Classification Positioning: pattern match, line match, circle match; Inspection : profile contrast, pixel counting, brightness , contrast; Identification : 1 dimensional and 2 dimensional codes ; Logic Tool: mathematical logic operation
	Focal Length	12 mm
	Focus Control	Auto focus
	Light Source Type	White (Red & Blue options) , 1-channel diffused and 2- channel transparent light
Performance	Working Distance	50-500mm
	Field of View	64×51 mm @150mm
	Max. Read Speed	60codes/s
	Max. Operating Speed	3m/s
Port	Connector	2 industrial M12 connectors, Ethernet and GPIO
	Network Port	100M Ethernet
	GPIO Interface	RS232, 2 Opto-isolated inputs , 3 Opto-isolated outputs
	Communication Mode	RS232, Ethernet
	Communication protocol	SDK,TCP Client,TCP Server, FTP,RS232,Profinet,Modbus, EtherNet/IP,MC(SLMP),FINS/UDP,FINS/TCP
	LED Indicator	Power, Ethernet, Result
Power	Power Supply	Support 9~26VDC, 1.5A input
	Power Consumption	<14W
Structure	Product Dimensions	47mm×58mm×38mm (excluding connectors)
	Net Weight	<180 g
	Protection	IP65
	Casing Material	Aluminum alloy (excluding front cover)
Environment	Operating Temperature	-20℃ ~ +50℃
	Operating Humidity	20% ~ 95%, non-condensing
	Storage Temperature	-30℃ ~ +70℃

Connector Pin-out

12 pin-out on camera:

Pin	Signal	Description	Cable Color	
1	OPT_OUT2	Opto-isolated output2		Brown white
2	RS232_TXD	RS232 serial send		Grey
3	RS232_RXD	RS232 serial receive		Purple
4	SIGNAL_GND	RS232 serial GND		Black white
5	OPT_IN1	Opto-isolated input1		Yellow
6	OPT_IN_GND	Opto-isolated input GND		Purple white
7	POWER	Power		Red
8	POWER_GND	Power GND		Black
9	OPT_OUT_GND	Opto-isolated output GND		Green
10	OPT_IN0	Opto-isolated input0		Orange
11	OPT_OUT0	Opto-isolated output0		Blue
12	OPT_OUT1	Opto-isolated output1		Brown
-	-	Shield GND		White

12-pin assignment on camera

